

NETRA SPARC T4-1

EXTREME SCALABILITY AND DENSITY WITH CARRIER-GRADE AVAILABILITY

KEY FEATURES

- NEBS™ Level 3 certification and ETSI compliance
- SPARC T4 processor is the industry's first processor designed for application network infrastructure workloads
- Enables up to 64 simultaneous execution threads using the SPARC T4 processor
- Redundant hot-swappable AC or DC power supplies and hot-pluggable disk drives
- Massive I/O performance

KEY BENEFITS

- Reliable operation in severe environmental conditions
- Built in no-cost virtualization technology with Oracle VM Server for SPARC and Oracle Solaris Zone
- Integrated on-chip cryptographic acceleration offers security for telecommunications data centers
- High reliability with an enhanced system uptime
- Cost efficiencies with reduced overall system power and cooling demands



Oracle's Netra SPARC T4-1 server is the first SPARC T4 processor based system with

throughput offering 2x the I/O bandwidth and 5x improvement in single threaded performance over the previous generation Netra SPARC server, all in a compact 20 inch deep 2 RU chassis. Designed to meet the most demanding telecommunication Web, media services, OSS/BSS, and BRM workloads, the Netra SPARC T4-1 is the ideal platform for consolidation and virtualization of the data center.

Product Overview

The Netra SPARC T4-1 server is powered by the SPARC T4 processor (8-core and 4-core) featuring integrated on-chip cryptographic support, providing wire speed encryption capabilities.

This server offers 16 DIMM slots, which can support a total of 256GB of memory, four hot-pluggable 2.5 inch drives plus DVD, integrated 10GbE networking, and built-in PCI Express Generation 2 expansion. Oracle Solaris and virtualization software such as the Oracle Solaris Zones and Oracle VM Server for SPARC technology make the Netra SPARC T4-1 a cost effective platform for large-scale telecommunication data center consolidation.

The Netra SPARC T4-1 provides a network infrastructure solution with carrier-grade reliability leveraging the chassis from previous generation, hot swappable components such as high efficiency AC or DC power supplies and disk drives. The Netra SPARC T4-1 comes integrated at no additional cost with Integrated Lights Out Manager (ILOM) service processor that offers industry-standard protocols for standalone system management as well as integration with many industry leading management systems.

Netra SPARC T4-1 Specifications

| Architecture |
|--|
| Processor <ul style="list-style-type: none"> • One 8-core 64 thread or one 4-core 32 threads 2.85GHz SPARC T4 processor • Up to 64 simultaneous threads per processor • Up to 8 floating point units • New chip Encryption Instruction Accelerators with direct non-privileged support for 16 industry-standard cryptographic algorithms plus random number generation in each of the eight-cores: AES, Camellia, CRC32c, DES, 3DES, DH, DSA, ECC, Kasumi, MD5, RSA, SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 • Oracle SPARC V9 architecture, ECC protected |
| Cache <ul style="list-style-type: none"> • Dedicated 128KB level 2 cache per core • Shared 4MB level 3 cache |
| Main Memory <ul style="list-style-type: none"> • Supports 8 GB and 16 GB DDR3 DIMMs • 16 DIMM slots, supporting a maximum of 256GB |
| Interfaces |
| Network <ul style="list-style-type: none"> • Four 10/100/1000 Base-T Ethernet ports • Up to two optional XAUI 10Gb Ethernet ports through optional 10 GbE Network Module |
| USB <ul style="list-style-type: none"> • Four 2.0 USB ports (rear and front) |
| Expansion Bus <ul style="list-style-type: none"> • Five PCIe Gen 2 x8 slots, 2x full-height/half-length, 3x low profile |
| Storage <ul style="list-style-type: none"> • Support for up to four optional internal 2.5-inch SAS disk drives, 10Krpm • Internal DVD: one slim line SATA DVD+/-RW • RAID level 0, 1 |
| Alarms <ul style="list-style-type: none"> • Four fail-safe, dry contact alarms—critical, major, minor, and user—DB-15 |
| Software |
| Operating System <ul style="list-style-type: none"> • Oracle Solaris 10 8/11 • Oracle Solaris 11 • Support for Solaris 10 9/10 and Solaris 10 10/09 with Oracle Solaris 10 8/11 Patch Bundle |
| Software Included <ul style="list-style-type: none"> • Oracle Solaris 11 • Oracle VM Server for SPARC |
| Virtualization <ul style="list-style-type: none"> • Built-in, no-cost Oracle VM Server for SPARC and Oracle Solaris Zones provide the flexibility and power of 64 virtual systems in a single Netra SPARC T4-1 server |
| Remote Management |

- Oracle Integrated Lights Out Manager (ILOM)
- Dedicated 10/100Base-T Ethernet network management port
- In-band, out-of-band and sideband network management access via any one of the four main Ethernet ports of the server
- One RJ-45 serial management port
- DTMF-style command-line interface
- Support for access via SSH 2.0, HTTPS, RADIUS, LDAP, and Microsoft Active Directory
- Browser-based GUI for control of the system through a graphical interface
- IPMI 2.0, SNMP v1, v2c, and v3
- Remote management with full keyboard, video, mouse, storage (KVMS) redirection and remote media capability (floppy, DVD, CD, and more)
- Ability to monitor and report system and component status on all FRUs

Power Supplies

- Two 1+1 redundant AC or DC hot-swappable power supplies
- Maximum DC power supply rating of 1200 W
- Maximum AC power supply rating of 1200 W

Environment

- DC Power: -48V DC or -60 V DC
- AC Power: 100-240 V AC, 50-60 Hz
- Operating Temperature: 5°C to 45°C (41°F to 113°F), short term -5°C to 55°C (23°F to 131°F)
- Operating Relative Humidity: 5%- 85% RH, non condensing, but not to exceed 0.024 kg water/kg dry air (0.053 lb. water/2.205 lbs. dry air)
- Short-Term Relative Humidity: 5%- 90% RH, non condensing, but not to exceed 0.024 kg water/kg dry air (0.053 lb. water/2.205 lbs. dry air)
- Operating Altitude: Meets NEBS 4,000 m (13,123 ft.) requirement
- Non-Operating Temperature: -40°C to 70°C (-40°F to 158°F)
- Non-Operating Relative Humidity: 93%, non condensing, 40°C (104°F)
- Non-Operating altitude: Up to 12,000 m (39,370 ft)
- Acoustic Noise: Operating/idling less than 7.2 B @ 23°C (LwAd: 1 B=10 dB)
- ETSI: EN 300019-2-1,2,3, Class 1.2, 2.3, 3.1E (except condensing humidity and rain)
- NEBS: NEBS Level 3 certified by Telecordia
- Seismic: GR-63-CORE requirements for earthquake Zone 4

Dimensions and Weight

- Height: 87.1 mm (3.43 in)
- Width: 445 mm (17.52 in) including mounting ears
- Depth: 526 mm (20.71 in) maximum to PSU handles
- Depth: 501 mm (19.72 in) maximum to rear I/O
- Weight: 18.6 kg (41 lbs) fully configured without PCI cards

Regulations

- Safety: EN 60950-1, IEC 60950-1 (Evaluated to all CB countries), UL 60950-1, CSA C22.2 No. 60950-1-07, IEC 825-1, 2 and CFR21 Part 1040
- EMI: EN55022 Class A, 47CFR15 Subpart B (FCC) Class A, ICES-003 Class A, AS/NZS CISPR22 Class A, CISPR22 Class A, EN300386 for Telecommunications Centers and for Other Than Telecommunications Centers
- EMC (immunity): EN55024, EN61000-3-2, EN61000-3-3, EN300386:2010 for Telecommunications Centers and for Other Than Telecommunications Centers
- Regulatory markings: CE, FCC, ICES-003, C-Tick, VCCI, GOST-R, KCC, UL/cUL, S-Mark, BSMI, CCC
- Other: Restriction of Hazardous Substances (RoHS) Directive and Waste Electrical and Electronics Equipment (WEEE) Directive

Warranty

The Netra SPARC T4-1 comes with a one-year warranty. For more information visit oracle.com/sun/warranty for Oracle's global warranty support.

Services

Only Oracle offers single point of accountability and complete, integrated support for the entire Oracle stack including 24/7 hardware service, expert technical support, proactive tools, and software updates. In addition to award-winning system support, Oracle also offers a portfolio of services that help install, configure, monitor and support your new Oracle Sun Netra servers utilizing Oracle best practices for higher availability and optimized system performance.

Visit oracle.com/support for information on Oracle's service program offerings for Sun products.

Contact Us

For more information about Netra SPARC T4-1, visit oracle.com or call +1.800.ORACLE1 to speak to an Oracle representative.



Oracle is committed to developing practices and products that help protect the environment

Copyright © 2013, Oracle and/or its affiliates. All rights reserved.

This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark licensed through X/Open Company, Ltd. 0112

Hardware and Software, Engineered to Work Together